

HYDRAULIC OILS



PRODUCT CODE	PRODUCT NAME	DESCRIPTION	SPECIFICATION		PACK SIZE
KH12	EP5 Hydraulic Oil	<p>Kanady hydraulic fluids are made from highly refined base oils with good oxidation resistance, lowering the possibility of gums and lacquers which would prevent the moving of the working parts. They contain carefully selected additives such as anti-oxidant; anti-corrosion to protect the system from corrosion should water be present and anti-wear to reduce wear in rotary pumps used in hydraulic systems. Kanady hydraulic oils are suitable for a wide variety of application and are recommended for rotary, vane, axial piston, gear pumps and bearings in many types of circulating systems.</p> <p>Benefits:-</p> <ul style="list-style-type: none"> - Incorporates the latest corrosion inhibitors for protection against all forms of corrosion - Highly shear stable - Good anti-foaming and air-release properties - Good demulsification characteristics - Good anti-wear performance for reduced wear in highly stressed vane pumps, highly loaded areas such as swash plates - High oxidation and thermal stability - Suitable for the majority of hose materials 	ISO	HM	BULK
KH11	EP10 Hydraulic Oil		DIN	51524 Part II HLP	
KH15	EP15 Hydraulic Oil		DENILSON	HF-0	
KH1	EP22 Hydraulic Oil		VICKERS	1-286-S M-2950-S	25/20
KH2	EP32 Hydraulic Oil		CINCINATTI MILICRON	P68 (ISO 32) P69 (ISO 68) P70 (ISO 46)	
KH3	EP46 Hydraulic Oil		FZG	Min Stage 11	
KH4	EP68 Hydraulic Oil				
KH5	EP100 Hydraulic Oil				
KH6	EP150 Hydraulic Oil				
KH14	Biolube 32		<p>Specialist premium quality, biodegradable high performance hydraulic fluids. Biolube 32 & 46 are manufactured from special rapeseed base stocks and specially selected additives to provide a fluid which is rapidly biodegradable. They are suitable for Agricultural, Forestry and Construction plant and equipment. They are <u>NOT</u> recommended for machinery fitted with wet brakes and clutches.</p>	DIN	53168
KH8	Biolube 46	Biodegradability - After 21 days		96%min	
		VDMA		24568	20
KH8/SE	Biolube SE46	<p>Synthetic ester based, biodegradable hydraulic fluid. Offers many advantages over vegetable based alternatives ie. more resistant to oxidation with a greatly reduced risk of gumming and varnish deposits, providing longer service life.</p>	ISO Denison	15380 HEES HF-2, HF-6	205 25
KH7	Poclain 46	<p>Poclain 46 is a high VI multigrade premium quality product. It may be used for the vast majority of heavy duty hydraulic oil applications. Genuine multigrade characteristics make the product suitable for use where hydraulic oils of ISO 32, 46 and 68 are normally recommended. The product is compatible with all materials normally found in hydraulic and related systems. It is dyed blue for identification purposes.</p>	ISO	HV	Bulk
			DIN	51524 Part III HVLP	
			DENILSON	HF-0	205
			VICKERS	1-286-S M-2950-S	
			POCLAIN	PO0552-13P	25
		FZG	Min Stage 12		