

INDUSTRIAL LUBRICANTS					
PRODUCT CODE	PRODUCT NAME	DESCRIPTION	SPECIFICATION		PACK SIZE
COMPRESSOR OILS					
KCO1	Kancom 32	A premium quality, low carbon forming compressor oil recommended for the lubrication of screw type compressors.	ISO	32	205
			DIN	51506 VD-L	20
KCO2	Kancom 46	A premium quality, low carbon forming compressor oil recommended for the lubrication of screw type compressors.	ISO	46	205
			DIN	51506 VD-L	20
KCO3	Kancom 68	A premium quality, low carbon forming compressor oil recommended for the lubrication of reciprocating (piston) type compressors. Kancom 68 can be used in sliding vane applications where oil of this viscosity is required.	ISO	68	205
			DIN	51506 VD-L	20
KCO4	Kancom 100	A premium quality, low carbon forming compressor oil recommended for the lubrication of reciprocating (piston) type compressors. Kancom 100 can be used in sliding vane applications where oil of this viscosity is required.	ISO	100	205
			DIN	51506 VD-L	20
KCO6	Kancom 150	A premium quality, low carbon forming, compressor oil. Kancom 150 is designed for reciprocating, screw and rotary compressor dependent upon viscosity requirements. 2000 hour drain periods are common with this type of lubricant.	ISO	150	20
			DIN	51506 VD-L	
KCO5	Hydrovane 4000	A premium quality, low carbon forming, semi synthetic compressor oil. Hydrovane 4000 is designed for reciprocating, screw and rotary compressor dependent upon viscosity requirements. 4000-hour drain periods are common with this type of lubricant. It is compatible with mineral oils.	ISO	46	25
			DIN	51506 VD-L	

INDUSTRIAL LUBRICANTS					
PRODUCT CODE	PRODUCT NAME	DESCRIPTION	SPECIFICATION		PACK SIZE
GEAR LUBRICANTS					
KI2	Kanlube 100	<p>A range of specially formulated extreme pressure industrial gear oils. The trend towards gear manufacture has resulted in higher capacity power transmission from smaller more compact units.</p> <p>Gear units can be divided into the following types:- Gears on parallel shafts - Spur, Helical and Herringbone. Gears on intersecting shafts - Straight and spiral bevel. Gears on crossed shafts - Skew, worm and hypoid.</p> <p>All of these might be lubricated by splash feed, pump feed or oil bath.</p> <p>To meet these varying demands, the Kanady range of industrial gear oils has been formulated using high quality solvent refined base oils and extreme pressure additives. They are available in varying viscosities to meet the exact demands of gearbox requirements.</p> <p>The Kanlube range can be recommended for most types of enclosed gear applications. They are also suitable for chain drives and bearings.</p>	ISO	68, 100, 150, 220, 320, 460	205
KI3	Kanlube 150				20
KI9	Kanlube 220		AGMA	250.04 & 9005-D94	205
KI5	Kanlube 320				20
KI16	Kanlube 460		DIN	51517 Part III	205
KI17	Kanlube 680				20
			David Brown	S1.53.101	205
		20			
SLIDEWAY OILS					
KI7	Kanslide 32	<p>A range of specially designed tacky slideway lubricants. The Kanslide range has been specially designed for machine tool slideway applications. They can be recommended for certain combined hydraulic and slideway systems. The lower viscosity grades are suitable for vertical slides and the higher viscosity grades are suited to horizontal slides. They include special tacky and lubricity additives, which afford good lubricity even at low traverse speeds. They can be also used as rock drill oils and pneumatic tool lubricants.</p>	ISO	32, 68, 220	205
KI8	Kanslide 68				20
KI4	Kanslide 220		DIN	51524 Part I	205
		20			